



Catalog Number
Notes
Type

Contractor Select™

# IVT

## Vapor Tight LED Strip Light

These fully-gasketed, wet-location, and code-compliant vapor tights are IP65, wet location rated. They can be surface mounted on the ceiling or wall or suspended using chain or aircraft cable. The IVT vapor tights are ideal for parking garages, canopies and utility areas.

### FEATURES:

- The fully gasketed, polycarbonate housing with stainless steel latches provides a water-tight seal and stands up to dust and dirt with its IP65 rating.
- The frosted polycarbonate lens provides uniform light output and solid impact-resistance. The fixture and lens are rated IK08.
- Quick and simple installation.
- Standard with Switchable technology: 4 lumen settings from 5000 to 7000 lumens. 3 CCT settings from 4000K to 6500K.



**RoHS**  
COMPLIANT



**WET**  
LOCATION™

**NOM**

Catalog Number	UPC	Description	Lumens	Wattage	Voltage	Color Temperature
IVT L48 AL029 IVOLT SWW10 80CRI M6	00197590522859	4' Switchable LED Vapor Tight Strip Light	5000/6000/7000 lumens	54	IVOLT (100-277)	40K/50K/65K

### Accessories in box

- Mounting Brackets x 2
- Machine threaded screw x 2
- V-hook x 2



## Specifications

### INTENDED USE:

Available in several color temperatures and lumen packages, all in one SKU. Ideal for use in commercial, retail, warehouse and canopy applications. **Certain airborne contaminants can diminish integrity of acrylic.** [Click here for Acrylic/Polycarbonate Environmental Compatibility table for suitable uses.](#)

Certain airborne contaminants may adversely affect the functioning of LEDs and other electronic components, depending on various factors such as concentrations of the contaminants, ventilation, and temperature at the end-user location. [Click here for a list of substances that may not be suitable for interaction with LEDs and other electronic components.](#)

### CONSTRUCTION:

- Light Gray Polycarbonate housing
- Frosted Polycarbonate lens
- Poured in place silicone gasket design
- Stainless steel latches.
- Standard 1/2" wet location fitting

### ELECTRICAL:

- IVOLT (100-277V)
- Non-Dimming standard
- Luminaire Surge Protection Level: Designed to withstand up to 2.5kV/0.75kA per ANSI C82.77-5-2015.

### INSTALLATION:

- Surface (wall, ceiling) using standard brackets; includes bail for chain hanging and suspend mounting.

### LISTINGS:

- NOM certified
- IP65 rated per IEC60529
- 2.5kV/0.75kA Surge Rated per ANSI C82-77-5-2015
- Rated for use in ambient temperatures -20° C to 40° C
- RoHS Compliant

### WARRANTY:

5-year limited warranty. This is the only warranty provided and no other statements in this specification sheet create any warranty of any kind. All other express and implied warranties are disclaimed. Complete warranty terms located at:

[www.acuitybrands.com/support/warranty/terms-and-conditions](http://www.acuitybrands.com/support/warranty/terms-and-conditions)

**Note:** Actual performance may differ as a result of end-user environment and application. All values are design or typical values, measured under laboratory conditions at 25 °C. Specifications subject to change without notice.

## Dimensions

All dimensions are inches (centimeters) unless otherwise indicated.

### 4FT ASSEMBLY

